

Maloney Oil Well Cementing Plugs

Rubber Body Cementing Plugs

Maloney Cementing Plugs are the most widely used plugs in the world. They are specially designed with a positive wiping action to ensure a clean casing. All rubber components are compounded and manufactured by Maloney to maintain high precision standards. Plugs are available in a wide variety of sizes and stocked for immediate shipment.

Top Plugs

The bottom section of the plug cup is designed to exert continuous pressure on the casing wall. The core is made of molded plastic for easy drilling. The tapered base fits the cavity of the bottom plug for a positive seal. Solid rubber top plugs are standard for 2-3/8" and 2-7/8" casing.

Bottom Plugs

Like the top plug, the fins and tail section provide positive wiping action. Fins also serve as a seal while cementing. The core of the bottom plug is hollow molded plastic. A rubber diaphragm at the top of the plug ruptures after the plug is seated allowing cement to flow through.

To order, just specify part number(s) listed in the specification table.



Visit our web site www.maloneytech.com

Rubber Body Cementing Plugs

Bottom Plug
Green

Top Plug
Black

Oil Well Cementing Plugs Sizes & Specifications

PART NUMBER	PART NUMBER	CASING SIZE	CASING WEIGHT	PLUG LENGTH	PLUG O.D.
TOP PLUG	BOTTOM PLUG				
450168332*	450168300	2-3/8"▼	4 / 5	4-1/2"	2-1/8"
450168338*	450168304	2-7/8"▼	5.9 / 6.5	5"	2-1/2"
450168320	450168308	3-1/2"▼	7.7 / 11.2	6"	3-1/8"
450168324	450168312	4"▼	9.25 / 11	6"	3-11/16"
450168234	450168203	4-1/2"	9.5 / 13.5	7-1/2"	4-3/16"
450168236	450168205	5"	11.5 / 21	8-1/2"	4-13/16"
450168238	450168207	5-1/2"	13 / 23	8-5/8"	5-5/16"
450168242	450168211	6-5/8"	17 / 32	9-1/4"	6-1/8"
450168244	450168213	7"	17 / 38	9-1/2"	6-5/8"
450168246	450168215	7-5/8"	20 / 39	10"	7-3/16"
450168248	450168217	8-5/8"	24 / 49	10-1/2"	8-1/8"
450168250	450168219	9-5/8"	29.3 / 53.5	11"	9-1/16"
450168252	450168221	10-3/4"	32 / 55.5	12"	10-7/32"
450168254	450168223	11-3/4"	38 / 61	13"	11-3/16"
450168256	450168225	12-3/4"	53	13-1/4"	12-1/4"
450168258	450168227	13-3/8"	48.0 / 83.5	15"	13"
450168260***	450168229	16"	55 / 84	19-1/2"	16-1/16"

* Solid Rubber Plug *** D'Ughm Core

▼ Denotes Tubing Size

Printed in USA

SALES & SERVICE WORLDWIDE

S&B TECHNICAL PRODUCTS
1300 East Berry Street
Fort Worth, Texas 76119 USA
Telephone 817.923.3344
Telefax 817.923.1339
U.S. & Canada 800.432.8213
www.hultec.com



HULTEC S.A.
De Empaques Santa Ana
Pozos de Santa Ana, Costa Rica
Telephone 506.282.9900
Telefax 506.282.2514

HULTEC EUROPE - PARIS
Maurepas, France
Telephone 33.1.30.507.252
Telefax 33.1.30.501.652

HULTEC ASIA PACIFIC - AUSTRALIA
St. Marys, NSW 2700
Telephone 61.2.98.339988
Telefax 61.2.98.339977

HULTEC - MEXICO
Tlalnepanitla, Estado de Mexico CP
Telephone 525.363.2483
Telefax 525.362.2324



MALONEY TECHNICAL PRODUCTS
1300 East Berry Street
Fort Worth, Texas 76119 USA
Telephone 817.923.3344
Telefax 817.923.1339
U.S. & CANADA 800.231.7236
email: sbtech@gte.net